

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Polyblend Ceramic Tile Caulk
PRODUCT CODE: PBC1K

HMIS CODES: H F R P
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Custom Building Products, Inc.
ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201
EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846
DATE REVISED : 2-04-99 NAME OF PREPARER : S. Taylor

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

COMPONENTS	CAS NUMBER	OSHA PEL	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE		WT. %
			ACGIH TLV		mm Hg @	TEMP	
ETHYLENE GLYCOL	00016721-1	50PPM	50PPM		.12mmhg	68	<1
BUTYL BENZYL PHTHALATE	85-68-7	5mg/m3	5mg/m3		8.6x10-4mmhg	68	7-8

* Indicates chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING POINT: 212F SPECIFIC GRAVITY (H2O=1): 1.25
VAPOR DENSITY: 15 mm Hg @ 25C EVAPORATION RATE: SLOWER THAN ETHER
SOLUBILITY IN WATER: MISCIBLE IN WATER.
APPEARANCE AND ODOR: WHITE OR COLORED PASTE WITH A SWEET BANANA ODOR.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA:
WATER, FOAM CARBON DIOXIDE OR DRY CHEMICAL.

SPECIAL FIREFIGHTING PROCEDURES
THE USE OF SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED. USE WATER TO COOL EXPOSED MATERIAL.

UNUSUAL FIRE AND EXPLOSION HAZARDS
KEEP WORK AREAS FREE OF HOT METAL SURFACE AND OTHER SOURCES OF IGNITION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID
N/A.

INCOMPATIBILITY (MATERIALS TO AVOID)
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
INHALATION: VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA, AND IRRITATION OF
THE NOSE, THROAT AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SKIN CONTACT: IRRITATING TO SKIN UPON REPEATED OR PROLONGED CONTACT.
EYE CONTACT: MAY CAUSE SLIGHT TRANSIENT (TEMPORARY) EYE IRRITATION.
CORNEAL INJURY IS UNLIKELY.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
Repeated skin exposure to large quantities may result in absorptions of
harmful amounts. The dermal LD50 has not been determined.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

HEALTH HAZARDS (ACUTE AND CHRONIC)
ACUTE:EYE CONTACT CAUSES SEVER IRRITATION. VAPORS MAY BE IRRITATING AND CAUSE
DIZZINESS, HEADACHE, NAUSEA, VOMITING, AND NARCOSIS.
CHRONIC:

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? YES
NOT LISTED AS A CARCINOGEN.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES
EYE CONTACT: IMMEDIATELY FLUSH WITH WATER FOR 15 MIN. SEE PHYSICIAN IF
IRRITATION RESULTS.
SKIN CONTACT: WASH WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS.
INHALED: IF AFFECTED, REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN
ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
INGESTION: IF SWALLOWED, SEEK MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

AVOID ENTRY INTO SEWERS OR NATURAL WATER WAYS.
SMALL SPILLS: SOAK UP WITH ABSORBANT MATERIAL.
LARGE SPILLS: DIKE AND PUMP INTO SUITABLE CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD
DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE
AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
STORE IN COOL, DRY AREA OUT OF SUNLIGHT.
STORE AWAY FROM HEAT OR ANY HEAT SOURCES. PROTECT FROM FREEZING.

OTHER PRECAUTIONS
NONE

===== SECTION VIII - CONTROL MEASURES =====
RESPIRATORY PROTECTION
IF EXPOSURE MAY EXCEED TLV RANGE, USE A NIOSH APPROVED RESPIRATOR
TO PREVENT OVEREXPOSURE.

VENTILATION
GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP
VAPOR CONCENTRATIONS WITHIN SPECIFIED TLV RANGES.

PROTECTIVE GLOVES
THE USE OF PLASTIC OR RUBBER GLOVES IS ADVISED TO PREVENT
SKIN IRRITATION OF SENSITIVE INDIVIDUALS.

EYE PROTECTION
SAFETY GLASSES ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
ADEQUATE CLOTHING SHOULD BE WORN TO PREVENT SKIN CONTACT.

WORK/HYGIENIC PRACTICES
GOOD HOUSEKEEPING PRACTICES SHOULD BE OBSERVED.

===== SECTION IX - DISCLAIMER =====

DISCLAIMER
THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT
WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT.
RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE
INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.